

C/Java Syntax

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

1

Lecture 02 Summary

- Keywords
- Variable Declarations
- Data Types
- Operators
- Statements
 - if, switch, while, do-while, for
- Functions

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

2

By the end of this lecture, you will be able to identify the different parts of a C program. You will also be able to create a simple C program.

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

3

What is a keyword?

What are some of the keywords in Python?

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

4

Keywords in C (all 32 of them)

auto	double	int	struct
break	else	long	switch
case	enum	register	typedef
char	extern	return	union
const	float	short	unsigned
continue	for	signed	void
default	goto	sizeof	volatile
do	if	static	while

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

5

Variable Declarations

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

6

In Python...

- which lines are okay?

```
lvar = 5
_pi = 3.1415
str+ing = "hello"
while = 3.3
x = '0'
myStr2 = "I'm a string"
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

7

C Variable Names

- Start with a letter or underscore
- Subsequent characters can also be numbers
- Can't use reserved keywords
- Case sensitive
 - `mystring` is not the same as `myString`

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

8

C Declarations

- Must specify the *type* of the variable (which will never change)

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

9

In Python...

```
x = 5 # x starts out as an integer
```

```
... more code ...
```

```
x = "now I'm a string"
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

10

In C...

```
int x = 5;
```

```
... more code ...
```

```
x = "Nooooooooooooooooo!"
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

11

Data Types

- Integral Types
 - char
 - short
 - int
 - long
 - long long
- Floating Point Types
 - float
 - double

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

12

Why isn't there just one `int` and one `float` type?

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

13

`sizeof` Operator

```
main()
{
    printf("int: %d bytes\n", sizeof(int));
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

14

In C...

- which lines are okay?

```
int lvar = 5
float _pi = 3.1415
short str+ing = "hello"
double while = 3.3
char x = '0'
int myStr2 = "I'm a string"
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

15

Operators

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

16

What are the operators?

```

int x = 5;
int y = x + 10;
int z = (x + 20) / y;

if (z < x)
    z = x * y;

```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

17

Operators in C

Operator	Description
++ --	postfix increment and decrement
()	function call
[]	array subscription
->	element selection through pointer
++ --	prefix increment and decrement
+ -	unary plus and minus
! ~	logical not, bitwise not
(type)	type cast
*	indirection/dereferencing of pointer
&	address of
sizeof	get the size of element
* / %	multiplication, division, modulus

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

18

Operators in C (cont'd)

Operator	Description
+ -	addition and subtraction
<< >>	bitwise shift left and right
< <= > >=	less than, less than equals, greater than, greater than equals
== !=	equals, not equals
&	bitwise AND
^	bitwise XOR (exclusive-or)
	Bitwise OR
&&	Logical AND
	Logical OR
<i>cond?t:f</i>	ternary command
= += -= *= /= %=	Assignment operators

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

19

Increment and Decrement

```
int i = 0;
int j = 10;
```

```
i = i + 1;
i++;
```

```
j = j - 1;
j--;
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

20

What will this output?

```
main()
{
    int x = 5;
    int y = 20;

    x++;
    y--;

    printf("x = %d\n", x);
    printf("y = %d\n", y);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

21

Prefix vs. Postfix

- Prefix = first thing that happens (before)
 - e.g., ++i
- Postfix = last thing that happens (after)
 - e.g., i++

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

22

Prefix vs. Postfix Example

```
main()
{
    int x = 5;
    int y = 5;
    int a;
    int b;

    a = x++; /* postfix */
    b = ++y; /* prefix */

    printf("a = %d\n", a);
    printf("b = %d\n", b);
    printf("x = %d\n", x);
    printf("y = %d\n", y);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

23

What will this output?

```
main()
{
    int i = 70;
    int j = 42;

    int a = i++ * ++j;

    printf("i = %d\n", i);
    printf("j = %d\n", j);
    printf("a = %d\n", a);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

24

Statements

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

25

In Python...

```
def fahrenheit_to_celcius(temp):
    return (temp - 32.0) * (5.0 / 9.0)

1 print "Enter the temperature in Farenheit:"
2 temp = input()

if temp < -459.67:
    print "It can't possibly be that cold!"
else:
    tempInCelcius = fahrenheit_to_celcius(temp)
    print "In Farenheit: %f" % temp
    print "In Celcius: %f" % tempInCelcius
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

26

Enter "72"

```

def fahrenheit_to_celcius(temp):
    5 return (temp - 32.0) * (5.0 / 9.0)

1 print "Enter the temperature in Farenheit:"
2 temp = input()

3 if temp < -459.67:
    print "It can't possibly be that cold!"
else:
    4 tempInCelcius = fahrenheit_to_celcius(temp)
    6 print "In Farenheit: %f" % temp
    7 print "In Celcius: %f" % tempInCelcius

```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

27

In C...

- Simple statements end with a semi-colon (;)
- Any *white space* is ignored by the computer
 - spaces, tabs, new lines
 - but is very helpful to *people* who read the code

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

28

if Statement Syntax

```
if (<conditional>
    <what-to-do-if-true>;
else
    <what-to-do-if-false>;
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

29

Example

```
main()
{
    int x = 3;

    if (x % 2 == 0)
        printf("x is even\n");
    else
        printf("x is odd\n");
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

30

Example

```
main()
{
    int x = 3;

    if (x % 2 == 0)
        printf("x is even\n");
    else
        printf("x is odd\n");
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

31

Example

```
main(){ int x = 3; if (x % 2 == 0)printf(
"x is even\n"); else printf("x is odd\n");}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

32

How would we write this in C?

```
if temp < -459.67:
    print "It can't possibly be that cold!"
else:
    tempInCelcius = fahrenheit_to_celcius(temp)
    print "In Farenheit: %f" % temp
    print "In Celcius: %f" % tempInCelcius
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

33

Would this work?

```
if (temp < -459.67)
    printf("It can't possibly be that cold!\n");
else
    tempInCelcius = fahrenheit_to_celcius(temp);
    printf("In Farenheit: %f\n", temp);
    printf("In Celcius: %f", tempInCelcius);
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

34

Compare it to this

```
if (temp < -459.67)
    printf("It can't possibly be that cold!\n");
else
    tempInCelcius = fahrenheit_to_celcius(temp);
printf("In Farenheit: %f\n", temp);
printf("In Celcius: %f", tempInCelcius);
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

35

Blocks

- Statements can be grouped together into a *compound* statement by enclosing them in curly braces ({})

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

36

Adjusted `if` Statement Syntax

```
if (<conditional>)
{
    <what-to-do-if-true>;
    <possibly>;
    <containing>;
    <multiple lines>;
}
else
{
    <what-to-do-if-false>;
    <also-more-lines>;
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

37

How would we write this in C?

```
if temp < -459.67:
    print "It can't possibly be that cold!"
else:
    tempInCelcius = fahrenheit_to_celcius(temp)
    print "In Farenheit: %f" % temp
    print "In Celcius: %f" % tempInCelcius
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

38

Answer

```
if (temp < -459.67)
{
    printf("It can't possibly be that cold!\n");
}
else
{
    tempInCelcius = fahrenheit_to_celcius(temp);
    printf("In Farenheit: %f\n", temp);
    printf("In Celcius: %f", tempInCelcius);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

39

Consider this code...

```
if (x > 50)
    if (y > 200)
        z = x * y;
else
    printf("error!\n");
```

- Which `if` does the `else` belong to?

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

40

Good Practice

```
if (x > 50)
{
    if (y > 200)
    {
        z = x * y;
    }
    else
    {
        printf ("error!\n");
    }
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

41

else if and switch Statements

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

42

What would this do?

```
int x = 3;

if (x == 1)
    printf("One!\n");
else
    if (x == 2)
        printf("Two!\n");
    else
        if (x == 3)
            printf("Three!\n");
        else
            printf("Not one, two, or three");
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

43

What would this do?

```
int x = 3;

if (x == 1)
    printf("One!\n");
else if (x == 2)
    printf("Two!\n");
else if (x == 3)
    printf("Three!\n");
else
    printf("Not one, two, or three");
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

44

switch Statement Syntax

```
switch (<variable>)  
{  
    case <value-one>:  
        <code>;  
        <code>;  
        break;  
  
    case <value-two>:  
        <code>;  
        <code>;  
        break;  
  
    default:  
        <code>;  
        break;  
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

45

Example

```
int x = 3;  
  
switch (x)  
{  
    case 1:  
        printf("One!\n");  
        break;  
    case 2:  
        printf("Two!\n");  
        break;  
    case 3:  
        printf("Three!\n");  
        break;  
    default:  
        printf("Invalid choice!\n");  
        break;  
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

46

Loops

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

47

Example

- Factorial
 - $n! = n \cdot (n-1) \cdot (n-2) \cdot \dots \cdot 3 \cdot 2 \cdot 1$

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

48

Complete this Python program

```
print "Enter a number greater than zero:"  
n = input()  
  
...
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

49

while Syntax

```
while (<condition>)  
    <statement>
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

50

What do you think this would do?

```
main()
{
    int i = 0;

    while (i < 10)
        printf("i = %d\n", i);
        i++;
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

51

Without the infinite loop

```
main()
{
    int i = 0;

    while (i < 10)
    {
        printf("i = %d\n", i);
        i++;
    }
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

52

Complete this C Program

```
main()
{
    int n;

    printf("Enter a number greater than zero: ");
    scanf("%d", n);

    ...
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

53

do-while Syntax

```
do
{
    <statement>;
    <statement2>;
} while (<condition>);
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

54

Compare

<code>int x = 5;</code>	<code>int x = 5;</code>
<code>while (x > 0)</code>	<code>do</code>
<code>{</code>	<code>{</code>
<code>printf("%d\n", x);</code>	<code>printf("%d\n", x);</code>
<code>x = x - 1;</code>	<code>x = x - 1;</code>
<code>}</code>	<code>} while (x > 0);</code>

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

55

for Syntax

```
for (<a>; <b>; <c>)
{
    <statements>
}
```

- <a> = Initialization of looping variable
- = Condition
- <c> = Modification of looping variable

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

56

For Loops

<code><a></code>	
<code>while ()</code>	<code>for (<a>; ; <c>;)</code>
<code>{</code>	<code>{</code>
<code><statements></code>	<code><statements></code>
<code><c></code>	<code>}</code>
<code>}</code>	

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

57

Example

```
int i;
for (i = 0; i < 5; i++)
{
    printf("%d\n", i);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

58

Complete this C Program

```
main()
{
    int n;

    printf("Enter a number greater than zero: ");
    scanf("%d", n);

    ...
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

59

Functions

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

60

Functions in C

- Must specify what type is returned
 - if there is no return statement, must return `void`
- Must specify the type of each parameter

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

61

Function Syntax

```
<return-type> function_name(<parameters>)  
{  
    <statements>  
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

62

Examples

```
int add(int x, int y)
{
    return x + y;
}

void print_int(int i)
{
    printf("%d\n", i);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

63

Remember from before

```
def fahrenheit_to_celcius(temp):
    return (temp - 32.0) * (5.0 / 9.0)
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

64

What would it look like in C?

```
def fahrenheit_to_celcius(temp):  
    return (temp - 32.0) * (5.0 / 9.0)
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

65

What would it look like in C?

```
float fahrenheit_to_celcius(float temp)  
{  
    return (temp - 32.0) * (5.0 / 9.0);  
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

66

What is main?

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

67

Variants of main

```
void main()  
{  
}
```

```
int main()  
{  
    return 0;  
}
```

```
int main(int argc, char **argv)  
{  
    return 1;  
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

68

Write this whole program in C

```
def fahrenheit_to_celcius(temp):
    return (temp - 32.0) * (5.0 / 9.0)

print "Enter the temperature in Farenheit:"
temp = input()

if temp < -459.67:
    print "It can't possibly be that cold!"
else:
    tempInCelcius = fahrenheit_to_celcius(temp)
    print "In Farenheit: %f" % temp
    print "In Celcius: %f" % tempInCelcius
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

69

Identify the different parts

```
int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}

void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

70

Keywords

```
int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}

void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

71

Variable Declarations

```
int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}

void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

72

Data Types

```

int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}

void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}

```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

73

Operators

```

int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}

void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}

```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

74

Statements

```
int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}

void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

75

Functions

```
int max(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

```
void main()
{
    int first;
    int second;
    int bigger;

    printf("Enter a number: ");
    scanf("%d", &first);
    printf("Enter another number: ");
    scanf("%d", &second);

    bigger = max(first, second);
    printf("The bigger number is: %d\n", bigger);
}
```

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

76

Create a Program in C

- Input:
 - three floating point numbers
- Output:
 - the average of those three numbers
- Use:
 - `scanf` to get the input
 - `printf` to show the result
 - a function to calculate the average

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

77

Lecture 02 Summary

- Keywords
- Variable Declarations
- Data Types
- Operators
- Statements
 - if, switch, while, do-while, for
- Functions

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

78

Next Class

- Arrays and Strings

January 13, 2009

Slides by Mark Hancock
(adapted from notes by Craig Schock)

79